


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM4040/BL		
POWER: 40W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 3473.3 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	3976	4066	4122	4096	4016	3939	3885	3914	0- 10	412.7	412.7	11.9
20	2650	2758	2814	2774	2651	2556	2513	2561	10- 20	931.8	1345	38.7
30	1573	1606	1623	1610	1584	1513	1502	1539	20- 30	932.9	2277	65.6
40	1044	1096	1097	1044	991.8	950.3	935.9	978.3	30- 40	821.9	3099	89.2
50	56.90	61.11	62.43	58.99	52.78	47.73	47.72	48.59	40- 50	317.9	3417	98.4
60	23.22	25.23	25.24	26.09	23.95	22.04	21.27	21.39	50- 60	30.72	3448	99.3
70	13.76	13.02	12.48	13.81	12.83	12.88	12.59	12.17	60- 70	16.74	3465	99.8
80	0.9345	0.7832	0.6476	0.7711	1.024	0.6212	0.6216	0.5934	70- 80	8.290	3473	100
90	0.1441	0.1428	0.1416	0.1389	0.2311	0.2245	0.2260	0.2247	80- 90	0.3256	3473	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:24 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```