


LAMP PHOTOMETRIC REPORT

MODEL: 93SS1030/BL		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 522.24 lm



$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%
10	1383	1373	1368	1381	1431	1469	1471	1435	0- 10	161.6	161.6	30.9
20	358.1	357.8	372.7	381.9	398.2	407.0	398.4	366.3	10- 20	224.7	386.3	74
30	95.14	89.73	86.01	89.82	100.4	95.93	93.35	90.95	20- 30	95.14	481.5	92.2
40	21.78	22.76	25.34	23.71	22.23	25.07	26.56	23.38	30- 40	29.64	511.1	97.9
50	4.128	3.992	3.668	3.763	3.839	4.035	4.045	3.908	40- 50	8.453	519.6	99.5
60	0.9460	1.059	1.241	0.9717	1.035	0.9885	0.9860	0.8493	50- 60	1.683	521.3	99.8
70	0.4892	0.7911	0.9924	0.3771	0.4155	0.4018	0.3790	0.3254	60- 70	0.7578	522.0	100
80	0.0272	0.0164	0.0082	0.0245	0.0217	0.0327	0.0436	0.0218	70- 80	0.2190	522.2	100
90	0	0	0	0	0.0054	0.0068	0.0082	0.0041	80- 90	0.0108	522.2	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3°C  
Operators:  
Test Date:29 August 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:



```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```