


LAMP PHOTOMETRIC REPORT

MODEL: 92TL206750W/BL		
POWER: 50W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5839.0 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2707	2732	2712	2674	2621	2584	2591	2645	0- 10	252.5	252.5	4.32
20	2756	2833	2748	2747	2649	2600	2597	2705	10- 20	762.0	1014	17.4
30	2384	2649	2398	2633	2457	2555	2404	2606	20- 30	1222	2236	38.3
40	1502	1874	1549	1960	1710	2021	1683	1957	30- 40	1359	3596	61.6
50	798.0	967.4	817.3	1057	935.1	1143	924.7	1060	40- 50	1029	4625	79.2
60	448.2	465.5	447.4	510.7	515.5	561.0	489.8	511.1	50- 60	621.2	5246	89.8
70	264.4	231.4	240.1	250.6	293.4	269.8	245.1	246.5	60- 70	358.0	5604	96
80	122.5	90.78	94.90	98.95	137.4	103.0	90.03	93.37	70- 80	184.4	5789	99.1
90	2.126	2.110	1.989	2.097	7.706	2.075	1.576	1.757	80- 90	50.44	5839	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:09 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```