


LAMP PHOTOMETRIC REPORT

MODEL: 93ZFLD6030/BL		
POWER: 60W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5517.4 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	5352	6014	6339	5378	4898	5489	6383	6126	0- 10	572.3	572.3	10.4
20	3779	4851	5742	4247	3507	4305	5887	4967	10- 20	1464	2036	36.9
30	2469	3519	3785	3055	1657	3152	3956	3658	20- 30	1827	3863	70
40	243.8	1613	1255	782.2	173.3	871.3	1368	1790	30- 40	1225	5088	92.2
50	59.42	167.3	229.8	76.13	41.52	85.24	247.8	201.3	40- 50	347.5	5436	98.5
60	19.46	27.25	44.66	17.31	14.34	18.21	49.09	29.32	50- 60	64.99	5501	99.7
70	5.593	5.910	6.591	3.082	1.520	3.206	7.548	6.095	60- 70	14.73	5515	100
80	0.2650	0.4035	0.4363	0.3016	0.2783	0.3085	0.3657	0.3090	70- 80	1.588	5517	100
90	0.1837	0.2134	0.3220	0.2470	0.2864	0.3398	0.3875	0.3016	80- 90	0.3151	5517	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:30 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```