

# ELMARK<sup>®</sup>

The Brand of Electricity

## TWO & FOUR LINES

### SKY TL2044

#### GENERAL INFORMATION »

- ∴ Rated voltage: 230V/ 50-60Hz
- ∴ Power: 6.5W
- ∴ Colour temperature: 2700K; 4000K; 6400K
- ∴ Colour: White; Black
- ∴ Body: Iron
- ∴ Lampholder: GU10
- ∴ Colour rendering index: Ra≥80
- ∴ Switch on/off: >20 000
- ∴ Long life: 30 000h
- ∴ Protection against dust and moisture: IP40

#### FEATURES »


- ∴ Completely replace traditional lighting fixtures
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Repeated switch on/off does not affect the lifespan
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Low heat emission
- ∴ Suitable for commercial sites, administrative buildings, banks, offices




## PRODUCT DETAILS »

Catalogue number WHITE	Catalogue number BLACK	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Length (mm)	Height (mm)
93TL2044/WH	93TL2044/BL	2 LINES EMPTY	-	-	-	56	86	135
93TL2044WW/WH	93TL2044WW/BL	2 LINES	6.5	585	2700	56	86	135
93TL2044W/WH	93TL2044W/BL	2 LINES	6.5	585	4000	56	86	135
93TL2044CW/WH	93TL2044CW/BL	2 LINES	6.5	585	6400	56	86	135
94TL2044/WH	94TL2044/BL	4 LINES EMPTY	-	-	-	56	86	135
94TL2044WW/WH	94TL2044WW/BL	4 LINES	6.5	585	2700	56	86	135
94TL2044W/WH	94TL2044W/BL	4 LINES	6.5	585	4000	56	86	135
94TL2044CW/WH	94TL2044CW/BL	4 LINES	6.5	585	6400	56	86	135

## ADDITIONAL INFORMATION »

 93TL2044WW/WH

 This luminaire is compatible with bulbs of the energy classes:

**A++**

**A+**

**A**


**B**

**C**

**D**


**E**

}



The luminaire is sold with a bulb of the energy class:

**A+**



874/2012

Catalogue number WHITE	Catalogue number BLACK	Packing/B ox (pcs)
93TL2044/WH	93TL2044/BL	1/80
93TL2044WW/WH	93TL2044WW/BL	1/80
93TL2044W/WH	93TL2044W/BL	1/80
93TL2044CW/WH	93TL2044CW/BL	1/80
94TL2044/WH	94TL2044/BL	1/80
94TL2044WW/WH	94TL2044WW/BL	1/80
94TL2044W/WH	94TL2044W/BL	1/80
94TL2044CW/WH	94TL2044CW/BL	1/80

