


LAMP PHOTOMETRIC REPORT

MODEL: 99POMT30/WH		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1435.6 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	539.6	538.6	538.2	538.8	534.7	534.9	537.0	541.1	0- 10	52.17	52.17	3.63
20	504.4	502.4	501.2	504.2	496.1	495.6	499.7	507.6	10- 20	147.3	199.5	13.9
30	448.9	451.3	444.8	452.7	445.0	436.7	442.7	454.6	20- 30	218.9	418.4	29.1
40	379.0	375.8	372.8	381.0	374.8	363.0	371.0	381.8	30- 40	257.8	676.2	47.1
50	302.5	293.4	290.9	298.3	293.4	282.7	289.7	300.5	40- 50	258.6	934.8	65.1
60	215.5	208.7	205.4	208.8	205.5	200.0	205.6	216.9	50- 60	224.7	1159	80.8
70	126.9	126.6	122.1	125.3	122.4	118.8	122.9	133.0	60- 70	164.6	1324	92.2
80	49.06	47.55	46.60	49.10	45.76	44.71	47.92	55.15	70- 80	89.91	1414	98.5
90	1.983	1.252	7.948	1.066	1.573	1.006	3.258	0.8967	80- 90	21.63	1436	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:15 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```